

Technical Sheet

alu[®]perf™ Perforations

- The perfect balance between maximum drainage and debris protection.
- Drains 29.7" (754 mm) of water per hour.
- Perforations measure 7/64" (2.8 mm).

roll@back™ Technology

- Keeps water from overflowing even when heavy rain flows down from the roof.

winter[®]shield™ Technology

- Prevents damage caused by ice and snow.
- Made of 0.017" aluminum.
- Will not rust.
- Will not warp.
- Recyclable.



Overlap

- Makes a perfect seal between sections.

flex[®] seal™ Technology

- Seals the back of the eavestrough/gutter tightly.
- U.V. rays and temperature variations resistant.
- Recyclable.



M-5100



- Adjustable back section for problematic installations.
- Adjustable for 4" eavestroughs/gutters (must cut perforated surface).

- M-5100 (5") and M-6100 (6"):
7.44' x 43 pcs = 320'
- MC-5100 (5" copper) and
MC-6100 (6" copper):
75' x 16 pcs = 120'


M-5300



- The traditional choice; fits most installations.

- M-5300 (5") and M-6300 (6"):
7.44' x 43 pcs = 320'

M-53ZIP



- 2-level surface; allows installation over screw-on hangers.

- M-53ZIP (5"):
7.44' x 43 pcs = 320'
- M-63ZIP (6"):
10' x 32 pcs = 320'
Available upon special request.